

## **ENGINEERED FOR DURABILITY**

# ArmaFlex Shield CX

The preferred insulation for outdoor applications.

- // Tough skin resistant to elements such as UV and humidity
- // Enable energy savings through protection against thermal losses
- // Innate barrier against water ingress

www.armacell.com.sg











#### TECHNICAL DATA - ARMAFLEX SHIELD CX

Brief description	Designed for outdoor applications, ArmaFlex Shield CX is an insulation material with a tough skin that is durable against elements su as UV and humidity.				
Property	Value / Assessment	Standard / Test method			
Temperature range					
Service temperature	Min. °C	Max. °C			
	-50	105			
Thermal conductivity					
Declared thermal conductivity	θm	0℃			
	$\lambda d \leq [W/(m \cdot K)]$	0.034			
	Remarks	Same as ArmaFlex Class 1			
ire Performance and Approval	s				
Burning behaviour of building materials and products	Flame retardant class B1 (foam mai	GB 8624			
Resistance to water vapour					
Water vapour diffusion resistance factor	µ ≥ 10000		GB/T 17794		
Other technical features					
Ageing stability	No obvious aging phenomenon in th	GB/T 16422			

F-series				H-series							
Pipe Ø [mm]	Item	Inner diameter (minimum) [mm]	Average thickness [mm]	Length [m]	Content [metric]	Pipe Ø [mm]	Item	Inner diameter (minimum) [mm]	Average thickness [mm]	Length [m]	Content [metric]
25	SH-F-025	25	9.25	2	96 m	6	SH-H-006	6	14	2	144 m
32	SH-F-032	32	9.25	2	72 m	10	SH-H-010	10	14	2	128 m
-	-	-	-	-	-	12	SH-H-012	12	14	2	112 m
-	-	-	-	-	-	15	SH-H-015	15	14	2	96 m
	-	-	-	-	-	20	SH-H-020	20	14	2	80 m
	-	-	-	-	-		SH- H-010-200				
-	-	-	-	-	-		SH- H-012-200				
-	-	-	-	-	-		SH- H-015-150				
-	-	-	-	-	-		SH- H-020-150				
-	-	-	-	-	-		SH- H-022-150		_		

#### M-series

Pipe Ø [mm]	ltem	Inner diameter (minimum) [mm]	Average thickness [mm]	Length [m]	Content [metric]	
22	SH-M-022	22	18.75	2	50 m	
25	SH-M-025	25	19.25	2	40 m	
28	SH-M-028	28	19.75	2	36 m	

#### Adhesives and Cleaners

Item	Description	Content [quantity]		
AS-AD520HL	12 cans of 500ml ArmaFlex 520 adhesive in a carton	12 tin		

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. Despite taking every precaution to ensure that said data and technical information are up to date, Armacell does not make any representation or warranty, express or implied, as to the accuracy, content or completeness of said data and technical information. Armacell also does not assume any liability towards any person resulting from the use of said data or technical information. Armacell reserves the right to revoke, modify or amend this document at any moment. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer.

At Armacell, your trust means everything to us, so we want to let you know your rights and make it easier for you to understand what information we collect and why we collect it. If you would like to find out about our processing of your data, please visit our Data Protection Policy.

Trademarks followed by ® or ™ are trademarks of the Armacell Group. © Armacell, 2023 All rights reserved

ArmaFlex | ArmaFlex Shield CX | Brochure | 052024 | en-SG

### ABOUT ARMACELL

As the inventor of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With more than 3,300 employees and 25 production plants in 19 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for acoustic and lightweight applications, recycled PET products, next-generation aerogel technology and passive fire protection systems.

