

SPECIFICATION SHEET



APPLICATIONS Refrigeration, Air conditioning and plumbing

INSTALLATION Tool-Free, Suited for horizontal pipe installation

- MATERIAL**
- Polypropylene
 - UV Resistant
 - Operating temperature -40° to 178°F (-40° to 81°C)
 - Paintable (preserves mechanical properties event after painting)
 - Non-adhesive surface for linear expansion of thermal insulation

CERTIFICATION UL classified for USA (UL-723 (ASTM E 84)) And ULC listed for Canada (ULC-S102.2).



COLOR SILVER GREY (G) BLACK (B) WHITE (W)

PART NUMBER	DESCRIPTION	A	B	C
UCX25B	12" Black InsuCover for I225B, I325B, I425B, I525B, I625B	12.02" (305mm)	0.83" (21mm)	0.41" (10mm)
UCX25W	12" White InsuCover for I225W, I325W, I425W, I525W, I625W	12.02" (305mm)	0.83" (21mm)	0.41" (10mm)
UCX50G	12" Grey InsuCover for IM250G, IM350G, IM450G, IM550G, IM650G	12.02" (305mm)	0.83" (21mm)	0.41" (10mm)
UC825B	12" Black InsuCover for I825B	12.02" (305mm)	0.83" (21mm)	0.41" (10mm)
UC825W	12" White InsuCover for I825W	12.02" (305mm)	0.83" (21mm)	0.41" (10mm)
UCL50G	18" Grey InsuCover for IM850G, IM1050G, IM1250G	18.02" (457mm)	0.77" (19.5mm)	0.41" (10mm)

