

# SPECIFICATION SHEET



**APPLICATIONS** Refrigeration, Air conditioning and Plumbing

## INSTALLATION

Tool-Free, "Clips" directly on standard 1-5/8" x 1-5/8" (42mm x 42mm) strut channel. Suited for horizontal pipe installation.

## MATERIAL

Polypropylene copolymer

- UV resistant
  - Operating temperature -40° to 178°F (-40° to 81°C)
  - Paintable (preserves mechanical properties even after painting)
  - Non-adhesive surface for linear expansion of thermal insulation.
- I825B & I825W have 20% glass filled material for additional strength

## CERTIFICATION

UL classified for USA (UL-723 (ASTM E 84)) And ULC listed for Canada (ULC-S102.2).



## COLORS



BLACK (B)



WHITE (W)

PART NUMBER	A	B	C	D	E
I225B	2.25" (57mm)	4.56" (116mm)	1.09" (28mm)	12" (30.5cm)	1-5/8" (42mm)
I225W	2.25" (57mm)	4.56" (116mm)	1.09" (28mm)	12" (30.5cm)	1-5/8" (42mm)
I325B	3.25" (82mm)	5.57" (140mm)	1.59" (40mm)	12" (30.5cm)	1-5/8" (42mm)
I325W	3.25" (82mm)	5.57" (140mm)	1.59" (40mm)	12" (30.5cm)	1-5/8" (42mm)
I425B	4.25" (108mm)	6.59" (167mm)	2.09" (53mm)	12" (30.5cm)	1-5/8" (42mm)
I425W	4.25" (108mm)	6.59" (167mm)	2.09" (53mm)	12" (30.5cm)	1-5/8" (42mm)
I525B	5.25" (133mm)	7.57" (192mm)	2.58" (66mm)	12" (30.5cm)	1-5/8" (42mm)
I525W	5.25" (133mm)	7.57" (192mm)	2.58" (66mm)	12" (30.5cm)	1-5/8" (42mm)
I625B	6.25" (159mm)	8.57" (218mm)	3.09" (78mm)	12" (30.5cm)	1-5/8" (42mm)
I625W	6.25" (159mm)	8.57" (218mm)	3.09" (78mm)	12" (30.5cm)	1-5/8" (42mm)
I825B	8.25" (204mm)	11.04" (280mm)	4.27" (108mm)	12" (30.5cm)	1-5/8" (42mm)
I825W	8.25" (204mm)	11.04" (280mm)	4.27" (108mm)	12" (30.5cm)	1-5/8" (42mm)

